

To prepare a PolaRx5 receiver for deployment with a UNACO based configuration perform the following steps. You will need to have the RxTools software package installed with a basic understanding of its operation. We will be using RxControl with the 'Expert Console' open to watch for errors. This process will work on Windows 7 and later or Fedora15 and later. Current browsers work well however problems have been reported when using older versions of Safari. See the KnowledgeBase article Safari Web Browser Incompatibility. For a detailed look at the configuration process see the complete guide Unav_PolaRx5_setup. A copy of the latest version of RxTools can be found at <http://www.septentrio.com/support>.

-Connect to the receiver using the COM1 serial connection. Use cable CBLe_COM_1.8 p/n 200416 to a serial port or use a serial to usb adaptor.

-If the receiver has been previously configured it should be cleaned up.

-To reset configuration to default.

GoTo 'File > Reset Receiver'

Select 'All' and 'OK'.

The Ethernet configuration is not reset with this command.

-To format the internal or external disk.

GoTo 'Logging > Disk Management'

Select appropriate disk, 'Format' and 'OK'.

-Load the current UNAV script. It can be downloaded from UNAVCO or you can paste the configuration text found below into a separate text file. This file will set up everything on the receiver except the user credentials and site metadata. The IP will be set to 192.168.1.2.

Once the configuration is loaded the IP can be changed for specific site requirements using the web GUI > Communications > Ethernet or RxControl > Communications > Network Settings. Changes to network setting do not take effect until a reboot is performed.

-If this receiver is being set up for PBO installation you will need to run the PBO user credentials script. The two scripts can be combined by appending the user credentials file to the end of the base file.

If using credentials other than PBO go to web GUI > Admin > User Administration or RxControl > File > User Management to create users and set passwords.

-Site metadata will be updated in during installation.

UNAV_X5_5-1-2_base_1.txt

```
# Review and comment out sections such as # Metadata or # Set receiver IP.  
# If the receiver has already been configured it is recommended you reset the receiver to  
default and format the internal drive.  
# Save data before reformatting.  
  
# Setup streams  
setSBFOutput, Stream1, LOG1  
setSBFOutput, Stream2, LOG2  
setSBFOutput, Stream3, LOG3  
setSBFOutput, Stream4, LOG4  
setSBFOutput, Stream8, LOG8  
setSBFOutput, Stream1, ,  
MeasEpoch+GPSNav+GPSIon+GPSUtc+GLONav+GALNav+GALUtc+GALGstGps+GEON  
av+PVTGeodetic+ReceiverSetup+ASCIIIn+CMPPNav+QZSNav  
setSBFOutput, Stream2, ,  
MeasEpoch+GPSNav+GPSIon+GPSUtc+GLONav+GALNav+GALUtc+GALGstGps+GEON  
av+PVTGeodetic+ReceiverSetup+CMPPNav+QZSNav  
setSBFOutput, Stream3, ,  
MeasEpoch+GPSNav+GPSIon+GPSUtc+GLONav+GALNav+GALUtc+GALGstGps+GEON  
av+PVTGeodetic+ReceiverSetup+CMPPNav+QZSNav  
setSBFOutput, Stream4, ,  
MeasEpoch+GPSNav+GPSIon+GPSUtc+GLONav+GALNav+GALUtc+GALGstGps+GEON  
av+PVTGeodetic+ReceiverSetup+ASCIIIn+CMPPNav+QZSNav  
setSBFOutput, Stream8, ,  
MeasEpoch+MeasExtra+EndOfMeas+OutputLink+GPSRawCA+GPSRawL2C+GPSRawL5  
+GLORawCA+GALRawFNAV+GALRawINAV+GALRawCNAV+GEORawL1+GEORawL5+  
GPSNav+GPSAIm+GPSIon+GPSUtc+GLONav+GLOAIm+GLOTIme+GALNav+GALAIm+G  
Allon+GALUtc+GALGstGps+GEONav+GEOAIm+BaseVectorGeod+PVTGeodetic+PosCov  
Geodetic+DOP+EndOfPVT+ExtEvent+DiffCorrIn+BaseStation+InputLink+ChannelStatus+  
ReceiverStatus+ReceiverSetup+Commands+CMPPRaw+IPStatus+QZSRawL1CA+QZSRaw  
L2C+QZSRawL5+PVTSupport+CMPPNav+QualityInd+NTRIPClientStatus+WiFiAPStatus+R  
xComponents+DiskStatus+RFStatus+IRNSSRaw+QZSNav+WiFiClientStatus+LogStatus+  
RxMessage  
setSBFOutput, Stream1, , , sec15  
setSBFOutput, Stream2, , , sec1  
setSBFOutput, Stream3, , , msec200  
setSBFOutput, Stream4, , , sec15  
setSBFOutput, Stream8, , , min2  
setBINEXOutput, Stream1, IPS1
```

```

setBINEXOutput, Stream1, , Rec0101+Rec05Geod+Rec7D00+Rec7E01+Rec7F05
setBINEXOutput, Stream1, , , sec1
setBINEXFormatting,
GPSL1CA+GPSL1PY+GPSL2PY+GPSL2C+GPSL5+GLOL1CA+GLOL2CA+GALL1BC+G
ALE6BC+GALE5a+GALE5b+GALE5+GEOL1+GEOL5+CMPL1+CMPE5b+CMPB3+QZSL1
CA+QZSL2C+QZSL5+IRNL5

# Setup Met/Tilt
setDataInOut, COM2, ASCIIIN
setPeriodicEcho, COM2, 'A:0R0%%CR%%LF'
setPeriodicEcho, COM2, , min5
setCOMSettings, COM2, baud19200

# Set up server port for streaming
#Leaving port set to 0 leaves it configured but disabled
#Set to 42042 for standard UNAV stream
setIPServerSettings, IPS1, 42042

# Set up IP filtering
setIPFiltering, , '192.168.1.0/24 10.0.0.0/8 69.44.86.0/23'

# Position
setPVTMode, Static

# Tracking
setMultipathMitigation, off
setMultipathMitigation, , off
setReceiverDynamics, , EarthquakeMon
setClockSyncThreshold, ClockSteering

# Metadata
setAntennaOffset, Main, , , 0.0083
setAntennaOffset, Main, , , , 'TRM59800.00    SCIT'
setMarkerParameters, 'pnnn'
setMarkerParameters, , 'pnnn'
setMarkerParameters, , , 'pnnn'
setMarkerParameters, , , , 'pnnn'
setMarkerParameters, , , , , 'USA'
setObserverParameters, 'UNAVCO'
setObserverParameters, , 'UNAVCO'

# Set filter and signal use
setSignalTracking,
GPSL1CA+GPSL1PY+GPSL2PY+GPSL2C+GPSL5+GLOL1CA+GLOL2CA+GALL1BC+G

```

```

ALE6BC+GALE5a+GALE5b+GALE5+CMPL1+CMPE5b+CMPB3+QZSL1CA+QZSL2C+QZ
SL5+IRNL5
setNotchFiltering, Notch1, off
setNotchFiltering, Notch2, off
setNotchFiltering, Notch3, off
setREFOUTMode, off
setSatelliteUsage,
G01+G02+G03+G04+G05+G06+G07+G08+G09+G10+G11+G12+G13+G14+G15+G16+G
17+G18+G19+G20+G21+G22+G23+G24+G25+G26+G27+G28+G29+G30+G31+G32+R01
+R02+R03+R04+R05+R06+R07+R08+R09+R10+R11+R12+R13+R14+R15+R16+R17+R1
8+R19+R20+R21+R22+R23+R24+R25+R26+R27+R28+R29+R30+E01+E02+E03+E04+E
05+E06+E07+E08+E09+E10+E11+E12+E13+E14+E15+E16+E17+E18+E19+E20+E21+E
22+E23+E24+E25+E26+E27+E28+E29+E30+E31+E32+C01+C02+C03+C04+C05+C06+C
07+C08+C09+C10+C11+C12+C13+C14+C15+C16+C17+C18+C19+C20+C21+C22+C23+
C24+C25+C26+C27+C28+C29+C30+C31+C32+C33+C34+C35+C36+C37
setSignalUsage,
GPSL1CA+GPSL1PY+GPSL2PY+GPSL2C+GPSL5+GLOL1CA+GLOL1P+GLOL2P+GLOL
2CA+GALL1BC+GALE5a+GALE5b+GALE5+CMPL1+CMPE5b
setSignalUsage,
GPSL1CA+GPSL1PY+GPSL2PY+GPSL2C+GPSL5+GLOL1CA+GLOL2CA+GALL1BC+G
ALE6BC+GALE5a+GALE5b+GALE5+CMPL1+CMPE5b+CMPB3+QZSL1CA+QZSL2C+QZ
SL5

# Setup sessions
setLogSession, LOG1, Enabled
setLogSession, LOG2, Enabled
setLogSession, LOG3, Enabled
setLogSession, LOG4, Enabled
setLogSession, LOG8, Enabled
setLogSession, LOG1, , , 'A'
setLogSession, LOG2, , , 'B'
setLogSession, LOG3, , , 'C'
setLogSession, LOG4, , , 'M'
setLogSession, LOG8, , , 'STATUS'
setLogSession, LOG1, , , , After1Year
setLogSession, LOG2, , , , After30Days
setLogSession, LOG3, , , , After7Days
setLogSession, LOG4, , , , After3Days
setLogSession, LOG8, , , , After4Days
setLogSession, LOG1, , , , , High
setLogSession, LOG2, , , , , High
setLogSession, LOG3, , , , , High
setLogSession, LOG4, , , , , High
setFileNaming, LOG1, IGS24H

```

```
setFileNaming, LOG2, IGS1H
setFileNaming, LOG3, IGS1H
setFileNaming, LOG4, IGS1H
setFileNaming, LOG8, IGS24H

# Set receiver IP
setIPSettings,Static,192.168.1.2,255.255.255.0,192.168.1.1

# copy config to Boot and User1
exeCopyConfigFile,Current,Boot
exeCopyConfigFile,Current,User1
#exeCopyConfigFile,RxDefault,User2
```

PBO_X5_5-1-2_user-admin_1.txt

You must edit the login un/pw for this script to work!

```
# Setup PBO Login Credentials
setUserAccessLevel, User1, 'pb0'
setUserAccessLevel, User1, , '8CODZDSFGI3FZS1TX1EQ62A98UR'

# Login to complete changes
login, un, pw

setUserAccessLevel, User2, 'unavco'
setUserAccessLevel, User2, , '814VI4ROF77L3QZ1ZDXFLOZPZU2'
setDefaultAccessLevel, Viewer
setDefaultAccessLevel, , Viewer
setDefaultAccessLevel, , , Viewer
setDefaultAccessLevel, , , , Viewer
setDefaultAccessLevel, , , , , Viewer

# copy config to Boot
exeCopyConfigFile,Current,Boot
exeCopyConfigFile,Current,User1
```