Vaisala Weather Transmitter WXT510

ORDER GUIDE (USD)

TOTAL VALUE

Weather Transmitter	v	/XT510 A	A								0	PRICE
Measurement parameters	Wsd+RH+T+P+R	A										\$1,98
•	Default setting		A								Ì	
Communication interface	SDI-12 v 1.3, 1200 baud, 7,E,1			Α								
	RS-232, Standard ASCII auto, 19200 baud,8,N,1			В								
	RS-485, Standard ASCII polled, 19200 baud, 8,N,1			С								
	RS-422, Standard ASCII auto, 19200 baud, 8,N,1			D								
	RS-422 NMEA 0183 v3.0, 4800 baud, 8,N,1			Е								
Heating	None				0							
	Heating for wind and rain measurements				1							\$9
Connector	No connector, bushing accessories					Α						
	8-pin M12 male connector and bushing accessories	(21519)))			В						\$
Cable	No cable						Α					
	2 meters long 8-pin M12 cable	(21519	1)				В					\$0
	10 meters long 8-pin M12 cable	(21519	3)				С					\$1
	40 meters long 8 wire cable, no connector, not for RS232	(21702	D)				D					\$3
Installation kit	None							0				
	Mounting Kit (adapts to US 3/4" pipe)	(21279)	2)					1				\$9
Supporting software	No configuration tool								0			
	Configuration tool (software and service cable)	(21519	4)						1			\$
Manual	No manual									Α		
	English									В		
Maintenance Contract	No										0	
										TOT		
Selections in bold are inclu-	uded in the prices of the basic versions.									C	ΩTY	

Selections in italic are available at an extra price.

Shaded sections indicate typical selections.

Example of order code with typical settings: WXT510 A A B 0 A A 0 0 B 0

Accessories and Spare Parts:	Description:	Order Code:	PRICE		
	WXT510 PTU Module Spare Part	WXT510PTUSP	\$210		
	Service cable only	215233	\$40		